# WE CREATE. WE INNOVATE.



## Neapolitan 130 (NP130W) Wood Fired Ovens



#### Overview

Our 130 Neapolitan Model, which is designed specifically to accommodate the high-volume pizza making of a true Pizzaiolo. The 130 features a 51.18 inch deck. The dome and deck consist of refractory bricks with 6.5 inches of multi-layered insulation in the dome and 8 inches in the deck. The oven features a 24 inch by 9.5 inch opening along with a stainless steel flue collar atop the dome.

The oven requires a 2" tolerance in all directions, and comes standard with a fire-rated tile clay dome. The 130 Neapolitan model also features a 14 inch landing on the opening, as well as a control located between the deck and the top of the dome for getting a precise reading. Oven can be vented directly to the roof or vented through a powered type 1 exhaust hood with approved exhaust duct in accordance with all local and national codes. For wood burning ovens, they must be vented as a solid fuel burning appliance and must be installed following a manner that obeys all local and national codes and is acceptable to authority having jurisdiction.

#### Pizza Capacity

Cooking Surface = 14.5 sq. ft. Pizza Capacity 8" = 14-16 Pizza Capacity 10" = 12-14 Pizza Capacity 12" = 6-7 Pizza Capacity 16" = 3-4

#### Standard Features

Standard Tile Selection
Door
Refractory Proprietary Brick Deck
High Temperature Flue Collar/Adapter
Steel Stand
Black Powder Coating
3 Year Deck and Dome Warranty
1 Year Parts and Labor Warranty

#### **Optional Features**

Tile Upgrade/Customized Logo Custom High-temp Vinyl Decal Custom Tile Applications Plug & Play Ventilation Powered Exhaust Fan Stainless Steel Mask/Stand Enclosed Facade Double Mouth Opening All Fuel Grease Duct Interior Lights Stainless Steel Oven Tools

#### Venting

The oven is vented through an 8" round duct collar. The Neapolitan gas ovens can be installed with a listed exhaust hood system or with a direct vent exhaust duct vented outside without an exhaust hood, but must be installed with a power exhausted vent. Cubic Feet per Minute: 150CFM Static Pressure: 0.01" W.C.

#### Clearance Requirements

2" Minimum clearance for Combustibles on all sides. 0" Minimum clearance for Non Combustibles.

## Shipping Dimensions

Actual Weight: 3,462 LBS Crated Weight: 4,524 LBS Crated Width: 96" Crated Depth: 83" Crated Height: 87"

## Approved






## WE CREATE.




Neapolitan 130 (NP130W) Wood Fired Ovens

## Top View




## Plan View




## Legend

- **C-**Controls
- E-Electrical Connection Flexible Cord
- F-Flue Collar
- **G-**Gas Connection
- S-Storage Shelf

## Front View



#### Side View



#### **Notes**

An ongoing program of product improvement may require us to change specifications without notice.

All ovens are designed to suit commercial usage.

Spec dimensions to be +/ - 0.50 inch.

Oven sizes refer to dome interior size.

All Marra Forni ovens are ETL, and VPN approved.

All oven Freight Class 77.5 and must be shipped LTL.

All Marra Forni ovens are approved with a door that is used as a fire suppressor. The door completely closes the front cavity of the oven. Sprinkler/ ansul systems not required.

Learn about gas, electrical, venting and clearance requirements at MARRAFORNI.





